

ECO-TRAP™ BLOC

GREASE TRAP TREATMENT BLOCK (SOFT, SHORT-TERM)

PRODUCT DESCRIPTION

ECO-TRAP™ BLOC is formulated as a soft, fast-dissolving blocks specifically designed for short-term or corrective treatment of grease traps that require immediate biological activation and grease breakdown. The latest version has increased wax content, enabling rapid release of active ingredients. It serves as a powerful complement to long-term products like BIOBLOC22™ (hard, long-lasting block) by providing immediate results when needed.

PACKAGING AND STORAGE

Available in 0.907 kg (2 pound) blocks (4/case) and 2.27 kg (5 pound) blocks (2/case). Each block is packaged in a mesh application bag.

Store in a cool, dry location. Packaging must be kept intact, dry, and away from sunlight. Please follow the recommendations and use the product before the best before date. Contact Bionetix® with questions. Avoid inhalation and eye contact. Avoid excessive skin contact.



FEATURES AND BENEFITS

- Ideal for shock treatments or corrective interventions
- Addresses grease and odor issues rapidly
- Serves as powerful complement to long-term treatments like BIOBLOC22™
- Keeps floats clean
- Reduces grease buildup
- Prevents emergency blockages
- Saves on line-jetting
- Lowers grease disposal costs
- Reduces bad odors

TYPICAL APPLICATIONS

- Removal of grease deposits and prevention of scum formation in holding tanks, sewers, drains, and aeration basins
- Acceleration of the biological degradation of wastewaters containing high levels of fat, oils, and greases (FOG)
- Reduction in the unpleasant odors associated with treatment plants handling fatty wastes

SPECIFICATIONS

| | |
|------------------|-------------------------------------|
| Description | Pink solid |
| Stability | Up to 24 months |
| pH | 7.9-8.9 |
| Bacteria Count | 3 billion CFU/g |
| Nutrient Content | Biological nutrients and stimulants |
| Bulk Density | Solid |

ECO-TRAP™ BLOC

APPLICATION INSTRUCTIONS

Add the ECO-TRAP™ BLOC directly to the grease trap.

Given its softer formulation, ECO-TRAP™ BLOC may dissolve faster in high-flow or turbulent conditions and possibly require biweekly replacement to ensure consistent treatment. Regular monitoring is recommended to ensure effective performance and timely replacement for continued treatment impact.

1. When locating ECO-TRAP™ BLOC in the grease trap, DO NOT place blocks directly into the flow of incoming sewage. The turbulence and “washing effect” will greatly reduce the longevity of this product. Ideally, the blocks should be placed in a less turbulent area of the grease trap, but not in a dead spot.
2. The blocks should be suspended in the grease trap so that they are always submerged in water, even at the lowest water level. This will assure maximum contact time with the organics, providing superior results.
3. If a grease shelf is present during placement of the blocks, raising the high level flow is recommended so that the bacteria can attack the grease shelf from the top, bottom, and sides.
4. Results should be obtained in four to eight weeks from the time of application. If grease shelves are present at the time of application, a longer period of time may be required to obtain results.

| Flow Rate | Dosage |
|---------------------------------|-------------------------------|
| 150-2000 L (50-500 gallons) | 0.907 kg (2 pounds) / 2 weeks |
| 2000-4000 L (500-1000+ gallons) | 2.27 kg (5 pounds) / 2 weeks |

For a flow rate of more than 4000 L (1000 gallons), please consult your Bionetix® representative.

The information presented in this product sheet is believed to be reliable. This information is provided as representative only and there are no warranties, expressed or implied, regarding its performance. Since neither distributor nor manufacturer has any control over handling, storage, use, or application conditions, they are not responsible for any claims, liabilities, damages, costs, or expenses of any kind arising out of or in any way connected with the handling, storage, or use of the product described. ISSUED DATE: 09/19/25. SUPERCEDES: 01/19/22.



**We Work
For Nature**



Bionetix® International Corporation, Inc.
21 040 rue Daoust, Ste-Anne-de-Bellevue, Quebec, Canada H9X 4C7
T. 514-457-2914 F. 514-457-3589
www.Bionetix-International.com

